ADMIXTURE RESIN MOISTURE SEALER

- Moisture resistance
- Excellent sealing affect to substrate
- Excellent bonding
- Enviromental, non toxic
- Reduced shrinkage and cracking
- Binding loose surface of particles
- Reduce absorption of substrate
- Alkaline resistance

US Miracle Moisture Sealer is a high performance polymer liquid admixture with high effectively penetration feature which is used as a moisture sealing on concrete surface. It can be used for surface pretreatment agent and surface enhancer for base plastering.

COMPLIED STANDARDS

Chinese Standard: JG/T 907-2002

USAGE

- Priming on concrete, blocks, cement based plaster or panel wall surface.
- Priming the base for render and screed.
- Surface treatment to substrate for receiving cementitious materials.

SURFACE PREPARATION

The surface must be cleaned from any kind of remnants, loose particles, dust, grease, etc.

APPLICATION

Mix US Miracle Moisture Sealer thoroughly before to use then apply it with a brush or roller onto the substrate surface. When the first coat is completely dry around 1-2 hours then apply a second coat, depending on the substrate and ambient conditions. The second coat must be applied after the first coat is dried for at least 4 hours. It is recommended to use US Miracle Tile Adhesive series products for tile installation or US Miracle Skim Coat series products for wall plastering.



WHITE LATEX ()

PACKING AND STORAGE

US Miracle Moisture Sealer is delivered in 200 Liters, 18 Liters, 5 Liters per drums. Shelf life is 12 months if the product is kept in a dry place in order to prevent them from moisture and sun.

The information detailed in this datasheet is liable to modifications from time to time in the light of experience & normal product development. To the best of our knowledge, the technical data contained herein are true. Because it is not possible to give specific instructions for various site conditions or control the applications. We reserve the right to modify the information detailed in this datasheet.

Www.USMiracle.com